



## **ACD SELECT DIESEL 15W40**

**UNIVERSAL MOTOROIL FOR GASOLINE AND DIESEL ENGINES.**

### **DESCRIPTION :**

ACD SELECT DIESEL 15W40 is a universal motoroil, suitable for all 4-stroke gasoline and diesel engines.

### **ADVANTAGES :**

- ✓ Very high resistance against oxidation.
- ✓ High detergent and dispersant properties.
- ✓ High neutralising power.
- ✓ Strong resistance.
- ✓ High lubrication power.
- ✓ Very large application field.
- ✓ Low loss by evaporation.

### **SPECIFICATIONS :**

API	SG/CE, CF-4, CF	VW	505.00
CCMC	G4/D4/PD2	MB	227.1
ACEA	A2-96 - Issue 2 / B2-98	MAN	271
	E2-96 - Issue 2	ALLISON	C4
MIL	MIL-L-2104 E	CAT	TO-2
	MIL-L-46152 D	VDS	VDS

### **APPLICATIONS :**

ACD SELECT DIESEL 15W40 is a universal motoroil, intended for the transport sector and the civil engineering, which may be used during the whole year. This oil is especially recommended for mixed fleets (passenger cars and vehicles). It can be used in all services during the whole year, in diesel engines with natural aspiration or with turbo discharge and in all gasoline engines, according to the severe prescriptions of Mercedes and VW.

ACD SELECT DIESEL 15W40 is also obtainable on semi-synthetic base, in order to meet specific requirements or severe working conditions.

### **TYPICAL CHARACTERISTICS :**

Test	Method	Unit	Average result
Class			15W40
Density at 15°C	D 4052	kg / m <sup>3</sup>	884
Viscosity at -20°C	D 5293	cP	6500
Viscosity at 40°C	D 445	cSt	105
Viscosity by 100°C	D 445	cSt	13,7
Viscosity index	D 2270		130
Pour point	D 97	°C	-34
TAN	D 2896	g KOH/kg	6,0
Flash point COC	D 92	°C	230
Sulphated ash	D 874	masse %	1,1

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.