



SUPER LONGDRAIN TURBO SAE 10W40

SEMI-SYNTHETIC MOTOR OIL U.H.P.D.

DESCRIPTION :

SUPER LONGDRAIN TURBO SAE 10W40 is a partially synthetic Ultra High Performance Diesel (UHPD) engine oil, meeting the highest performance standards for large trucks.

APPLICATIONS :

SUPER LONGDRAIN TURBO SAE 10W40 is intended for truck fleet operators, seeking the best available lubricating oil technology, in order to meet the increasingly stringent emission limits that are imposed on diesel engines in Europe, especially for the EURO-2-engines.

SPECIFICATIONS :

SUPER LONGDRAIN TURBO SAE 10W40 provides the following performance in a SAE 10W40 viscosity grade:

API	CF	VOLVO	VDS-2
ACEA	E4-99	SCANIA	LDF
MB	228.5	MACK	EO-L
MAN	M 3277	RENAULT	RXD

TYPICAL CHARACTERISTICS :

Test	Method	Unit	Average result
SAE-class			10W40
Density at 15°C	D 4052	kg / m ³	876
Viscosity at -25°C	D 2602	cP	6100
Viscosity at 40°C	D 445	cSt	88
Viscosity at 100°C	D 445	cSt	13,5
Viscosity index	D 2270		155
Flash point COC	D 92	°C	220
Pour point	D 97	°C	-36
TBN	D 2896	g KOH/kg	14,1
Sulphated ash	D 874	mass %	1,9
Loss by evaporation	NOACK	mass %	12,5

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.