



ACD SELECT SAE 40

MOTOR OIL ONLY FOR DIESEL ENGINES.

DESCRIPTION :

ACD SELECT SAE 40 is a monograde motor oil, primarily intended for diesel engines, with or without turbo.

ADVANTAGES :

- ✓ Very high resistance against oxidation.
- ✓ High detergent and dispersant properties.
- ✓ High neutralizing power.
- ✓ Strong resistance.
- ✓ High lubrication power.
- ✓ Very large application field.

SPECIFICATIONS :

API	SJ/CF-4, CF	MB	228.0
ACEA	E2-96 - Issue 2	MAN	270

APPLICATIONS :

ACD SELECT SAE 40 is a motor oil, suitable for fixed diesel engines for power generation or heavy trucks, working in warm climatic conditions.

TYPICAL CHARACTERISTICS :

Test	Method	Unit	Average result
SAE-class			SAE 40
Density at 15°C	D 4052	kg / m ³	892
Viscosity at 40°C	D 445	cSt	140
Viscosity at 100°C	D 445	cSt	15
Viscosity index	D 2270		108
Pour point	D 97	°C	-27
TBN	D 2896	g KOH/kg	7,3
Flash point COC	D 92	°C	248
Sulphated ash	D 874	mass %	1,01

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.