



ACD SPDA ISO 46

HYDRAULIC ANTI-WEAR OIL.

DESCRIPTION :

ACD SPDA ISO 46 is a mineral oil, especially designed to meet the requirements of the most important constructors of hydraulic equipment.

ADVANTAGES :

- ✓ Contains anti-wear, anti-oxidant, anti-corrosion and antifoam additives.
- ✓ Is distinguished by its desemulsinating power, a high viscosity index, a low pour point and a long lifetime.

SPECIFICATIONS :

AFNOR 48600	DENISON
ASLE 70-1	DIN 51524 Part 2
70-2	VDMA 24318
70-3	SPERRY VICKERS M2950-SD
DAVID BROWN ET 19	SPERRY VICKERS I-286-S3
DAVID BROWN ET 33	US STEEL 126/127

APPLICATIONS :

ACD SPDA ISO 46 is especially designed to satisfy the requirements of the manufacturers of hydraulic systems where the highest demands are made concerning high pressure, temperatures or speeds.

ACD SPDA ISO 46 is recommended for the hydraulic systems of the following types : VICKERS, GEROTOR, GRESEN, HPM, DENISON, CESSNA, HYDRECO, WORTHINGTON, etc.

ACD SPDA ISO 46 is also suitable for the lubrication of workshop equipment, reducing gears, bearings, compressed air systems and air screw compressors.

TYPICAL CHARACTERISTICS :

Test	Method	Unit	Average result
ISO-grade			46
Density at 15°C	D 4052	kg / m ³	875
Viscosity at 40°C	D 445	cSt	46,6
Viscosity at 100°C	D 445	cSt	7
Viscosity index	D 2270		107
Pour point	D 97	°C	-33
Flash point COC	D 92	°C	220
TAN	D 974	g KOH/kg	0,2

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

4006

July, 2004.