



ACD SUPREME PLUS 5W30

DESCRIPTION :

ACD SUPREME PLUS 5W30 is a fully synthetic engine oil of the latest generation, for the lubrication of all gasoline and diesel engines with turbo, giving fuel economy benefits.

ADVANTAGES :

- ✓ Excellent fluidity at low temperature.
- ✓ Very low resistance at start.
- ✓ Exceptional viscosity index.
- ✓ Very high thermal stability.
- ✓ Fuel Economy formulation.

SPECIFICATIONS :

API	SL/CF
ACEA	A3-02/B3-98#2/B4-02
VW	502.00 / 505.00
MB	229.3

APPLICATIONS :

- ✓ 4-stroke gasoline engines, multi-valves, turbo.
- ✓ 4-stroke diesel engines, with or without turbo.

TYPICAL CHARACTERISTICS :

Test	Method	Unit	Average result
SAE-class			5W30
Density at 15°C	D 4052	kg / m ³	853
Viscosity at 40°C	D 445	cSt	72
Viscosity at 100°C	D 445	cSt	11,9
Viscosity at -30°C	D 5293	cP	5500
Viscosity index	D 2270		162
Pour point	D 97	°C	-39
TBN	D 2896	g KOH/kg	10
Flash point COC	D 92	°C	214
Loss by evaporation	NOACK	mass %	9,0
Sulphated ash	D 874	mass %	1,0

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

14115

August, 2005.