



## **ACD SUPREME PLUS LONGLIFE III 5W30**

### **DESCRIPTION :**

ACD SUPREME PLUS LONGLIFE III 5W30 is a 100% synthetic, fuel economy "low SAPS" motoroil of the latest generation, which is especially developed to meet the "long life III" requirements of the cars of the constructors Volkswagen, Audi, Skoda and Seat.

### **ADVANTAGES :**

- ✓ Lower service costs by lower fuel consumption
- ✓ A longer working life for exhaust gas treatment systems ("low saps")
- ✓ Fuel economy because of low viscosity of the oil.
- ✓ Very strong protection against wear. Good lubrication at cold start.
- ✓ Very good detergency and dispersion.

### **SPECIFICATIONS :**

Meets the VW-norms 504.00 and 507.00. These norms exceed almost all the previous specifications: 502.00 / 503.00 / 503.01 / 505.00 / 506.00 and 506.01.

ACEA        A3/B4 and C3

### **APPLICATIONS :**

- ✓ This oil can be used in all vehicles with extended oil drain intervals, except in V10 TDI and the 5 cylinder 2,5 TDI engines.
- ✓ The first generation engines with pump injector units have to use the 505.01 specification.

### **TYPICAL CHARACTERISTICS :**

Test	Method	Unit	Average result
SAE-klasse			5W30
Density at 15°C	D 4052	kg / m <sup>3</sup>	849
Viscosity at 40°C	D 445	cSt	70
Viscosity at 100°C	D 445	cSt	11.5
Viscosity at -30°C	D 5293	cP	5600
Viscosity index	D 2270		159
Flash Point COC	D 92	°C	230
Pour Point	D 97	°C	-39
TBN	D 2896	g KOH/kg	5.8
Sulphated ash	D 874	%	0.6

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.