



# TRUCK 30-40

## PRODUCT DESCRIPTION

*XTREME TRUCK 30 and TRUCK 40 are premium quality monograde lubricants blended with selected mineral base oils and additives.*

*They are appropriate where multigrade lubricants are not preferred.*

*These products give following main benefits:*

- *high oxidation resistance.*
- *very good antiwear protection*
- *excellent detergency/dispersancy properties*

## APPLICATIONS

*XTREME TRUCK 30 and TRUCK 40 are premium monograde lubricants for vast majority of diesel engines in farm equipments requiring API SF/CD quality level.*

## SPECIFICATIONS

### API SF/CD

#### TYPICAL CHARACTERISTICS (\*)

Product Designation	TRUCK 30	TRUCK 40
SAE Viscosity Grade	30	40
Density at 15°C, ASTM D 1298, Kg / dm <sup>3</sup>	0,875	0,880
Viscosity at 40°C, ASTM D 445, cSt	85	104
Viscosity at 100°C, ASTM D 445, cSt	10.0	13,5
Viscosity Index , ASTM D 2270	101	100
Pour Point, ASTM D 97, °C	-18	-15
Flash Point , ASTM D 93 ,°C	220	224

(\*) The reported figures are typical of those obtained with normal production tolerance and therefore may be subjected to variation; they do not constitute a specification, exception made for SAE VG