



XTREME 7001

PRODUCT DESCRIPTION

XTREME 7001 5W-30 is an advanced performance synthetic engine oil designed to provide exceptional cleaning power, wear protection and overall performance. XTREME 7001 5W-30 has been expertly engineered to help prolong the life and maintain the efficiency of Car Emission Reduction Systems in both diesel and gasoline powered automobiles. XTREME 7001 5W-30 exceeds the requirements of many leading industry and car manufacturers' standards required for newer modern diesel and gasoline powered passenger car engines.

APPLICATIONS

XTREME 7001 5W-30 is made with a proprietary blend of leading edge components formulated to be fully compatible with the latest Diesel Particulate Filters (DPF's) and Gasoline Catalytic Converters (CAT's). XTREME 7001 5W-30 has been designed to deliver outstanding performance and protection in conjunction with improved fuel economy. This lubricant gives longer engine life and shows following main benefits:

- *Excellent low temperature fluidity that gives fast oil flow on start up*
- *high oxidation resistance which reduces deposit formation*
- *good detergency/dispersancy properties giving cleaner engines*
- *enhanced engine protection against wear*

SPECIFICATIONS

API SM/CF
MB 229.5
BMW LONG LIFE 01-04

ACEA A3/B3/B4
VW 504.00 / 507.00
PORSCHE

TYPICAL CHARACTERISTICS (*)

7001 5W30	METHOD	VALUE
SAE Viscosity Grade		5W/30
Density at 15°C, Kg / dm ³	ASTM D 1298	0,850
Viscosity at 40°C, cSt	ASTM D 445	72.8
Viscosity at 100°C, cSt	ASTM D 445	12.1
Viscosity Index	ASTM D 2270	164
Pour Point, °C	ASTM D 97	-45
Flash Point , °C	ASTM D 92	250

(*) The reported figures are typical of those obtained with normal production tolerance and therefore may be subjected to variation; they do not constitute a specification, exception made for SAE VG.